

MICRO-POLLO LED

GROUND OR WALL MOUNT

TYPE:

PROJECT NAME:

MODEL #

FINISH

OPTICS

ACCESSORY

VOLTAGE




MICRO-POLLO LED

FEATURE


- Versatile aiming angle 0°-180° vertical tilting and 350° horizontal rotation adjustability.
- Die-cast aluminum housing with tempered glass, silicone gaskets, stainless steel hardware.
- IP65 rated.

APPLICATION


- Ideal for lighting to emphasize architectural details.
- Application areas: facade, lighting sculptures, architectural enhancement, highlighting plants, trees, signage.




MICRO-POLLO LED



L143139.93 - WARM WHITE LED 3300 °K 3W



L143139.95 - COOL WHITE LED 6800 °K 3W



SPECIFICATION SHEET

ACCESSORIES

-  **L142375** -PROTECTIVE GRILL
(Available in color 10,29)
-  **L142378** - VISOR in die-cast aluminum
(Available in color 10,29)
-  **L142373** - SPIKE in plastic
-  **L142478** - IP65 Extension signal cable (length:1000)
-  **L142479** - IP65 Extension signal cable (length:2000)

METAL FINISH

- 10. BLACK** **29. GREY(OUTDOOR)**

OPTICS

- F. FLOOD 40°** **S. SPOT 15°**

VOLTAGE

- 120V** **220V**

LEDOLOGY®

A **Luminart**® BRAND

WWW.LUMINARTLIGHTING.COM