SLIM
Projectors

TYPE:

PROJECT NAME:

SLIM

- Corpo in alluminio pressofuso EN AB-46100
- Staffa di fissaggio in acciaio inox 304.
- Die-cast EN AB-46100 aluminium housing
- Fixing bracket in stainless steel 304.
- Powder paint in 2 step process:
  - surface treatment containing ceramic nano particles (Bonderite);
  - polyester powder paint with high resistance against UV rays and corrosion certified Qualicoat®.
- Tempered glass diffuser.
- Stainless steel screws A4.
- Epdm gasket
- Single cable entry with nikel-brass cable blocker IP68 for cable with diam 5-12 mm.
- Lamp not included (except led version).
- The led modules can't be replaced in the fixture (UE 874/2012 norms).
- IP66, Class I
- In according to EN60598-1 norms and relative specifications.

SPECIFICATION SHEET

SLIM
Projectors

TYPE:

PROJECT NAME:

MODEL #	FINISH	LED COLOR	OPTIC	DRIVER	VOLTAGE
	–	–	–	–	–

Configuration code
L228294 + .1 + .28

Finishing

.1 Anthracite grey

.4 Aluminum grey

.8 Corten

Accessories

L2270 Galvanized peg

L228294

LED 13w 1700 lumen
4000°K CRI>80
120-277v 50/60Hz

IP66 CL I
Ik08



L228302

LED 34w max 3500 lumen
4000°K CRI>80
120-277v 50/60Hz

IP66 CL I
Ik08

Dimmable version

1-10V



SPECIFICATION SHEET