

# TECH


Recessed Ground/Wall

TYPE:

PROJECT NAME:



## TECH



Inox Aisi 316L

- Housing in die-cast aluminium ENAB46100
- Painted with polyester powders certified Qualicoat® previous treatment of sandblast process and hexavalent chrome free passivation
- Tempered glass diffuser
- Closing screws in stainless steel A4
- Silicone rubber gaskets
- Junction box in polycarbonate V1 (850°C) for version with control gear outside the fitting, rolled tube in thermoplastic material
- Lamp not included
- IP67, IK09 shock resistance (IK10 inox version)
- Class I
- CE omologations

# TECH

## Recessed Ground/Wall

TYPE:

PROJECT NAME:

MODEL #

FINISH

LED COLOR

OPTIC





DRIVER

VOLTAGE




Configuration code  
**L221077 + .4 + .01**

**Finishing**

-  **.01** Frosted glass
-  **.1** Anthracite
-  **.4** Grey (Ral 9006)
-  **.16** Inox ring (Aisi 316)

**Accessories**



-  **L22104** Connector IP68



**L221076**  
Pavimento - Ground - Sol

35w 3600 lumen  
4000°K CRI 70  
220-240V 50/60Hz

IP67 



SPECIFICATION SHEET