



MODEL #	FINISH	LED COLOUR	OPTIC	WATTAGE	DRIVER	VOLTAGE
---------	--------	------------	-------	---------	--------	---------




Segnapasso da incasso a parete, ideale per l'illuminazione di gradini e corridoi.
Recessed wall spotlight, ideal for the lighting of steps and corridors.

Materiale	Corpo in alluminio anticorodal N° 2 finiture standard
N° Led	1 x 1/2W
Potenza assorbita	1/2W
Collegamento	In serie rispettando la polarità
Cablaggio	Fornito con 25 cm di cavo
Installazione	- Muratura con scatola da incasso 503 (non inclusa) e viti M3 a scomparsa (fornite) - Cartongesso/Legno con molle (non incluse)
Driver switching	(non inclusa) 350mA (1W) p. 424 (non inclusa) 500mA (2W) p. 425
Accessori	Molla cod. ML060 p. 402

Material	Anticorodal aluminium body No. 2 standard finishings
Led no.	1 x 1/2W
Power absorption	1/2W
Connection	Series connection respecting polarities
Wiring	Provided with a 25cm long cable
Installation	- On brickwork through a 503 box (not included) and screws M3 (included) - On false ceiling/wood with springs (not included)
Driver switching	(not included) 350mA (1W) p. 424 (not included) 500mA (2W) p. 425
Accessories	Spring code ML060 p. 402

alisea

IP40 CE M M F III kg 0,400



CODE	OPTIONS	SUPPLY	N°LED	LED COLOUR	OPTICS	WATT	FINISHING
L6ALI	... 0	... I CC	... 1	... 1 6000°K 2 4000°K 3 3000°K W 2700°K 4 Red 5 Green 6 Blue	... 1 15°	... 1 2	... A Anod. alu. B White RAL9003

SPECIFICATION SHEET