

# ARGON

RECESSED LED

TYPE:

PROJECT NAME:



MODEL #      FINISH      LED COLOUR      OPTIC      WATTAGE      DRIVER      VOLTAGE




Faretto da incasso a pavimento, ideale per l'illuminazione di marciapiedi, vialetti, giardini.  
Recessed floor spotlight, ideal for the lighting of sidewalks, paths, gardens.

|                          |   |
|--------------------------|---|
| <b>Materiale</b>         | Corpo in alluminio anticorrosivo anodizzato<br>Flangia in acciaio inox lavorato o satinato<br>Diffusore in PMMA sabbato<br>N° 2 finiture standard |
| <b>N° Led</b>            | 1 x 1/2W (Forma S) - 3 x 1/2W (Forma M)   |
| <b>Potenza assorbita</b> | 1/2W (Forma S) - 3/6W (Forma M)   |
| <b>Collegamento</b>      | In parallelo  |
| <b>Cablaggio</b>         | Fornito con 50 cm di cavo in neoprene e pressacavo  |
| <b>Installazione</b>     | A pavimento con cassaforma (non inclusa)  |
| <b>Alimentatore</b>      | (non inclusa) 24V dc p. 427   |
| <b>Accessori</b>         | Cassaforma (1 LED) cod. CA031 p. 398<br>Cassaforma (3 LED) cod. CA061 p. 399  |
| <b>Note</b>              | Equipaggiato con D.O.B. System  |

|                         |  |
|-------------------------|--|
| <b>Material</b>         | Body made of anticorrosive anodized aluminium<br>Top made of worked/ satinized stainless steel<br>Satinized PMMA diffuser<br>No. 2 standard finishings |
| <b>Led no.</b>          | 1 x 1/2W (Option S) - 3 x 1/2W (Option M)  |
| <b>Power absorption</b> | 1/2W (Option S) - 3/6W (Option M)  |
| <b>Connection</b>       | Parallel connection  |
| <b>Wiring</b>           | Provided with a 50 cm long neoprene cable + cable gland  |
| <b>Installation</b>     | On the floor with housing box (not included)   |
| <b>Power supply</b>     | (not included) 24V dc p. 427   |
| <b>Accessories</b>      | Housing box code CA031 (1 LED) p. 398<br>Housing box code CA061 (3 LED) p. 399   |
| <b>Note</b>             | Equipped with D.O.B. System  |


## argon S



IP67 CE F III kg 0,250 2000 WP

| CODE         | OPTIONS        | SUPPLY      | N°LED    | LED COLOUR  | OPTICS        | WATT                 | FINISHING   | DIMMER          |
|--------------|----------------|-------------|----------|---|---------------|----------------------|---|-----------------|
| <b>L6ARG</b> | ...            | ...         | ...      | ...   | ...           | ...                  | ...   | ...             |
|              | <b>S</b> 1 LED | <b>V</b> CV | <b>1</b> | <b>1</b> 6000°K<br><b>2</b> 4000°K<br><b>3</b> 3000°K<br><b>W</b> 2700°K<br><b>4</b> Red<br><b>5</b> Green<br><b>6</b> Blue | <b>6</b> 360° | <b>1</b><br><b>2</b> | <b>I</b> Worked steel<br><b>S</b> Satinized steel | <b>D</b> Dimmer |

## argon M



IP67 CE F III kg 0,500 2000 WP

| CODE         | OPTIONS        | SUPPLY      | N°LED    | LED COLOUR  | OPTICS        | WATT                 | FINISHING   | DIMMER          |
|--------------|----------------|-------------|----------|---|---------------|----------------------|---|-----------------|
| <b>L6ARG</b> | ...            | ...         | ...      | ...   | ...           | ...                  | ...   | ...             |
|              | <b>M</b> 3 LED | <b>V</b> CV | <b>3</b> | <b>1</b> 6000°K<br><b>2</b> 4000°K<br><b>3</b> 3000°K<br><b>W</b> 2700°K<br><b>4</b> Red<br><b>5</b> Green<br><b>6</b> Blue | <b>6</b> 360° | <b>1</b><br><b>2</b> | <b>I</b> Worked steel<br><b>S</b> Satinized steel | <b>D</b> Dimmer |

SPECIFICATION SHEET

LEDODOLOGY®

A Luminart® BRAND

WWW.LUMINARTLIGHTING.COM