



MODEL #	FINISH	LED COLOUR	OPTIC	WATTAGE	DRIVER	VOLTAGE
---------	--------	------------	-------	---------	--------	---------



Faretto da incasso a parete/ pavimento, ideale per l'illuminazione di gradini, mensole, scaffalature, parquet e superfici in legno.


Recessed wall/ floor spotlight, ideal for the lighting of steps, shelves, parquet and wooden surfaces.

Materiale	Corpo in alluminio anticorodal Vetro temperato sabbiato N° 3 finiture standard
N° Led	1 x 1W
Potenza assorbita	1W
Collegamento	In serie rispettando la polarità
Cablaggio	Fornito con 25 cm di cavo
Installazione	Cartongesso/legno: per interferenza tramite o-ring (fornito) o con molle <i>(non incluse)</i>
Driver switching	<i>(non inclusa)</i> 350mA (1W) p. 424
Accessori	Molla cod. ML025 p. 402
Fotometrie	p. 406

Material	Anticorodal aluminium body Satinized tempered glass No. 3 standard finishings
Led no.	1 x 1W
Power absorption	1W
Connection	Series connection respecting polarities
Wiring	Provided with a 25 cm long cable
Installation	On false ceiling/wood through o-ring (included) or springs <i>(not included)</i>
Driver switching	<i>(not included)</i> 350mA (1W) p. 424
Accessories	Spring code ML025 p. 402
Photometries	p. 406

ecco

IP44 CE M M F III kg 0,015 kg 250 ø mm 27



CODE	OPTIONS	SUPPLY	N°LED	LED COLOUR	OPTICS	WATT	FINISHING
L6ECO	... 0	... I CC	... 1	... 1 6000°K 2 4000°K 3 3000°K W 2700°K 4 Red 5 Green 6 Blue	... 4 120°	... 1	... A Anod. alu. B White RAL9003 C Chromium-plated

SPECIFICATION SHEET