



MOK



MOK

- Extruded aluminium body 6060T5
- Closing terminal in die-cast aluminium with high oxidation resistance (ENAB44300)
- Aluminium fixing support
- Painted with polyester powders certified Qualicoat® previous treatment of sandblast process and hexavalent chrome free passivation
- Tempered glass diffuser
- Closing screws in stainless steel A4
- Silicone rubber gasket
- Lamp not included
- IP65, IK07 shock resistance
- Class I
- CE omologations

MOK

Projectors

TYPE:

PROJECT NAME:

MODEL #

FINISH

LED COLOR

OPTIC

DRIVER

VOLTAGE



Finishing



.01 Anthracite



.4 Grey (Ral 9006)



.8 Corten

Accessories





L2270 Galvanized peg

Configuration code
L223770 + .1 + .28 + .32

L223770

Projectors

20w 1700 lumen
4000°K CRI 80
120-277V 50/60Hz



MOK



SPECIFICATION SHEET

LEDOLOGY®

A Luminart® BRAND

WWW.LUMINARTLIGHTING.COM

MOK

Projectors LED

TYPE:

PROJECT NAME:

L223770

MODEL #


FINISH

LED COLOR


OPTIC

DRIVER


VOLTAGE



VISTA LATERALE - SIDE VIEW



VISTA FRONTALE - FRONT VIEW



BASSETTA DI FISSAGGIO - FIXING SUPPORT

SPECIFICATION SHEET

Housing:

Extruded aluminium body 6060T5, Die-cast aluminium ring with high oxidation resistance ENAB 44300, Fixing flask in aluminium.

Diffuser:

Transparent tempered glass diffuser

Closing screws:

Screws in stainless steel A4

Rubber gasket:

Silicone rubber gaskets

Wiring:

Brass cable blocker IP68 of nickel plated M16 for cable @4.5-10mm.

Installation:

Projectors

Weight:

1.80 Kg

Finish:

.1 anthracite, .2 white, .4 grey aluminium, .8 corten

Accessories:

L2271 plastic peg L22104 connector IP68.

LED Driver Voltage Options:

120-277V

SOURCE DESCRIPTION

LED Options:

.27 4000°K .28 3000°K. .29 6000°K. .31 beam 10° .32 beam 40°

CRI:

CRI 85

Rated luminous flux:

Lighting flow: 1100 lumen. Total assorbed power 18w.

CERTIFICATIONS

Normative:

EN60598 and relative specifications

Certification:

ETL

Protection Class:

IP65-IK08

Insulation Class:

Class I

SPECIFICATION SHEET

LEDOLOGY®

A **Luminart** BRAND

WWW.LUMINARTLIGHTING.COM