

X ONE

Bulkhead Downlight

TYPE:

PROJECT NAME:

MODEL #

FINISH

LED COLOR

OPTIC

DRIVER

VOLTAGE



Body and fixing plate made of die-cast aluminium alloy, corrosion resistant.

Protection by means of iridite, epoxy powder base coating and polyester painting.

5mm extra-clear flat tempered glass cover.

Product with no visible screws and completely hidden fixing plate.

Protection rating: IP65

Breaking strength: IK 05

Corps et base en aluminium moulé sous pression résistant à la corrosion.

Protection de l'ensemble par traitement d'iridite avec primaire aux poudres époxy et peinture polyester.

Diffuseur en verre trempé plat extra-clair de 5mm d'épaisseur.

Sans vis apparente, fixation murale invisible.

Degré de protection: IP65

Résistance à la rupture: IK 05

SPECIFICATION SHEET



1



2



3



4



5

NOTES

- 1 . No visible screws with closing screws
- 2 . Wall fixing plate hidden in the body
- 3 . IP 65 protection rate with IP 66 integral cable gland
- 4 . Extra-clear glass (for maximum light transmission)
- 5 . Availability of high brightness Multichip versions

NOTES

- 1 . Sans vis apparentes avec grains de fermeture
- 2 . Fixation murale dissimulée dans le corps
- 3 . Degré de protection IP 65 avec presse-étoupe intégré IP 66
- 4 . Verre extra-clair (transmission optimale de la lumière)
- 5 . Des versions Multichip à haute luminosité sont disponibles

LEDOLOGY®

A **Luminart** BRAND

WWW.LUMINARTLIGHTING.COM

ONE Bulkhead Transparent glass - *ONE Plafonnier Verre transparent*

.02 .06 .09




1 LED Multichip

Code	Description	Version	∠°	Power Supply	Lumen	Cl
L15 15 513	1 LED x 17W	3000K	2 x 23°	220-240V 0/50/60Hz	1750	I
L15 15 563	1 LED x 17W	4000K	2 x 23°	220-240V 0/50/60Hz	1900	I





L15 15 619	HIT-TC-CE 20W	G8,5		220-240V 0/50/60Hz	1700	I
------------	---------------	------	--	--------------------	------	---


L15 15 639	TC-TE 18W	GX24q-2		220-240V 0/50/60Hz	1200	I
------------	-----------	---------	--	--------------------	------	---



526 cd/klm



385 cd/klm



ONE Bulkhead Sandblasted glass - *ONE Plafonnier Verre sable*



1 LED Multichip


Code	Description	Version	∠°	Power Supply	Lumen	Cl
L15 16 513	1 LED x 17W	3000K	2 x 23°	220-240V 0/50/60Hz	1750	I
L15 16 563	1 LED x 17W	4000K	2 x 23°	220-240V 0/50/60Hz	1900	I



L15 16 619	HIT-TC-CE 20W	G8,5		220-240V 0/50/60Hz	1700	I
------------	---------------	------	--	--------------------	------	---

L15 16 639	TC-TE 18W	GX24q-2		220-240V 0/50/60Hz	1200	I
------------	-----------	---------	--	--------------------	------	---

SPECIFICATION SHEET



LEDOLOGY®

A **Luminart**® BRAND

WWW.LUMINARTLIGHTING.COM