

SLITT 2

RECESSED LED

TYPE:

PROJECT NAME:



MODEL # FINISH LED COLOUR OPTIC WATTAGE DRIVER VOLTAGE




Segnapasso da incasso a parete, ideale per l'illuminazione di scale, corridoi, ingressi.
Recessed wall spotlight, ideal for the lighting of stairs, corridors, entrances.

Materiale	Corpo in acciaio verniciato N° 3 finiture standard
N° Led	1 x 1/2W
Potenza assorbita	1/2W 2/3W (230V ac)
Collegamento	- In serie rispettando la polarità - A rete 230V ac
Cablaggio	Fornito con 25 cm di cavo
Installazione	Muratura con scatola da incasso 503 (non inclusa) e viti di fissaggio M3 a scomparsa (fornite)
Driver switching	(non inclusa) 350mA (1W) p. 424 (non inclusa) 500mA (2W) p. 425
Fotometrie	p. 423

Material	Varnished steel body No. 3 standard finishings
Led no.	1 x 1/2W
Power absorption	1/2W 2/3W (230V ac)
Connection	- Series connection respecting polarities - 230V ac
Wiring	Provided with a 25cm long cable
Installation	On brickwork through a 503 box (not included) and screws M3 (included)
Driver switching	(not included) 350mA (1W) p. 424 (not included) 500mA (2W) p. 425
Photometries	p. 423

slitt 2

IP20 CE M/M F III Supply I Supply R kg 0,300 POWER SUPPLY mm 40x32x26



CODE	OPTIONS	SUPPLY	N°LED	LED COLOUR	OPTICS	WATT	FINISHING
L6SL2
	Q Square	I CC	1	1 6000°K 2 4000°K 3 3000°K W 2700°K 4 Red 5 Green 6 Blue	3 60°x10°	1 2	B White RAL9003 O Black RAL9005 R Cor-ten
L6SL2
	Q Square	R 230V ac	1	1 6000°K 2 4000°K 3 3000°K W 2700°K 4 Red 5 Green 6 Blue	3 60°x10°	1 2	B White RAL9003 O Black RAL9005 R Cor-ten

SPECIFICATION SHEET

LEDOLOGY®

A Luminart® BRAND

WWW.LUMINARTLIGHTING.COM