

PASSUM SIDEWARDS

Ground and wall recessed, ground surface light.



Ø 70 **LED**
2.76"



Ø 125 **LED**
4.92"



Ø 180 **LED**
7.09"



PASSUM adjustable

Ground recessed, adjustable optic



Ø 180 **LED**
7.09"

PASSUM SIDEWARDS

Ground + wall recessed, sideways emitting

GENERAL FEATURES

A range of recessed luminaires in primary low copper content aluminium alloy, painted in double coat polyester powders after phosphochrome, resistant to UV rays and harsh weather conditions.

Dimensions: \varnothing 70/125 and 180mm(7.09").

Remote driver for \varnothing 70 mm(2.76"), inside for 125(4.92") and 180mm(7.09").

Side-emitter optic to turn the light along the ground surface.

Led 1/3/4 and 9,5W / CRI 80.

Life: 50.000 h with max decreasing of 30% - L70 B50.

Vandalproof polycarbonate diffuser and surface $T \leq 40^{\circ}\text{C}$ for each model.

Max load pressure allowed 2.000 Kg.

Walk over + driver over allowed.

Light body supplied pre-wired with 0,5 mt in-ground cable H07RN-F and connection block IP68.

The covering canopies are supplied separately, in copper free aluminium with double layer of powders painting, resistant to any bad weather conditions, stainless steel screws.

Four different light emissions 90° / $2 \times 90^{\circ}$ / 180° and 360° .

The version d 180mm(7.09") with fully adjustable optic from 0° to 45° towards up becomes a minimally invasive accent light.

Made according to EN 60598-1:08+A11:09 European standards **CE**

MAXIMUM MODULARITY


The lighting fittings of the range are supplied in 3 separate parts:

- 1 - Recessing box
- 2 - Light body with glass and gasket
- 3 - Ground/wall drive over canopy.




SIDE EMITTER OPTIC

The lens turns the light and orient the along the ground surface.



LIGHT BODY HORIZONTAL REGULATION

After inserting the light body in the recessed box is possible a complete planning regulation, to level out the fitting.



IN-GROUND WIRING

Any fitting of the range is pre-wired with 0,5 mt H07RN-F cable and IP 68 connection block IP 68.




WALK OVER AND DRIVE OVER

Max surface $T \leq 40^{\circ}\text{C}$ and load pressure max 2.000Kg.



CHANGEABLE CANOPIES IN ALUMINIUM

The covering canopies allows to orient the light in 4 different light emissions: 90° / opposite 90° / 180° and 360° angle beam.



PASSUM SIDEWARDS ø180 (7.09")




Ground + wall recessed for surface light

TYPE: _____

PROJECT NAME: _____


| IN-GROUND BOX



CODE	/ DESCRIPTION
1431	/ In-ground box ø 180 mm (7.09")

In-ground box in waterproof technopolymer.

| LIGHT BODY ø 180 mm (7.09")




CODE	/ LAMP	/ OPTIC	W	Lm
1436	○ Led	-	9,5	1200

Driver inside 120V / 350 mA.
T_s ≤ 40°C and max load pressure 2000 Kg.
IK 10 / IP 67 / Class I / 4000K / CRI 80

For 3000 K add TC to the code n.



| COVERING CANOPIES ø 180 mm (7.09")




CODE	/ DESCRIPTION
1535	/ 1 window
1536	/ 2 windows 90°
1537	/ 2 windows 180°
1539	/ 360° Light


COLOUR **GM**




1 window



2 windows 90°



2 windows 180°



360° Light

A richiesta l'insieme corpo lampada+flangia viene fornito montato e sigillato.
The set light body+flange can be supplied assembled, sealed and oriented.