

# LATY

WALL/CEILING LED SYSTEM

TYPE:

PROJECT NAME:



SPECIFICATION SHEET



105°



3000K / 4000K



40



>80



A+



0



Matte black



Satin white



# LATY

WALL / CEILING SYSTEM

*Characterized by a dark cut on its surface, which contrasts with the light cast from the sides of the luminaire, Laty is a modular double emission luminaire for wall or ceiling. It is made from epoxy polyester powder coated aluminium and it is equipped with a frosted polycarbonate screen and LED light sources. This fixture requires a 24Vdc remote driver (to be ordered separately) which, for maintenance purposes, must be placed in an inspection box at a distance of no more than 10 metres. Its degree of protection against the penetration of dust, solid objects and liquids is IP40.*

**LEDOLOGY**<sup>®</sup>

A **Luminart** BRAND

WWW.LUMINARTLIGHTING.COM

# LATY

## WALL/CEILING LED SYSTEM



TYPE:

PROJECT NAME:

LATY

CODE	W	Lm (3000K)
L25A7-603.L100...*	2x12 (2x120 led)	2x1200
L25A7-603.L100...*	2x25 (2x280 led)	2x2500
L25A7-004L	End caps (pair)	
L250800/DIM	Dimming kit	
L250800/EM	Emergency kit with batteries	

\*code per meter  
remote driver not included



Multiples of 50 mm\*, max length 4m Cod. L25A7-603.L

Multiples of 30 mm\*, max length 4m Cod. L25A7-604.L

\*NOTICE: add 17,4 mm on the total length of the composition.

SPECIFICATION SHEET