

# FRAME EX PLUS 2

WINDOW/ARCHWAY HIGHLIGHTER


TYPE:

PROJECT NAME:


## FRAME EX PLUS 2



Material	Anticorodal aluminium body	
	PMMA lens	
Abs. Power	C.C.	1 x 3W
	24Vdc 230 version	1 x 4W
Connection	Standard version	C.C. Series 24Vdc Parallel
	120 version	120Vac Mains voltage
Wiring	Provided with 2 m cable	
Installation	On ground with mounting base and set screws (included)	
Power supply	3W - 700mA (Not included)	
	4W - 24Vdc (Not included)	
	4W - 120Vac (Integrated)	
Finishing		.01 Anodized aluminium
		.02 Matt white RAL9003
		.08 Matt black RAL9005
		.09 Corten
		.17 Anthracite
Also available		5000 K
		Red
		Green
		Blue
	Customized cable length	



FRAME EX PLUS 2 120V



SPECIFICATION SHEET




# FRAME EX PLUS 2

WINDOW/ARCHWAY HIGHLIGHTER

TYPE:

PROJECT NAME:

## FRAME EX PLUS 2



IP65 CE kg 0,47

	SUPPLY	W	LM	OPTICS	LED COLOR	CODE	+	FINISHING
	C.C.	3	220	3° x 115°	3000 K	L01ECA11135	.01 .02 .08 .09 .17	
	C.C.	3	240	3° x 115°	4000 K	L01ECA11145	.01 .02 .08 .09 .17	
	24Vdc	4	220	3° x 115°	3000 K	L01ECA11235	.01 .02 .08 .09 .17	
	24Vdc	4	240	3° x 115°	4000 K	L01ECA11245	.01 .02 .08 .09 .17	

POWER SUPPLIES REQUIRED:

**700mA (3W) IP65 - IP67**

DE70014 [14W] (1/4 Fixtures)


**24Vdc (4W) IP67**

AE24018 [18W] (1/3 Fixtures)

AE24035 [35W] (1/7 Fixtures)

AE24060 [60W] (1/12 Fixtures)

## FRAME EX PLUS 2 120V



IP65 CE kg 0,52

	SUPPLY	W	LM	OPTICS	LED COLOR	CODE	+	FINISHING
	120Vac	4	220	3° x 115°	3000 K	L01ECA21335	.01 .02 .08 .09 .17	
	120Vac	4	240	3° x 115°	4000 K	L01ECA21345	.01 .02 .08 .09 .17	

*Power supply integrated*

SPECIFICATION SHEET