

OLA

LED Exterior

TYPE:

PROJECT NAME:

Ola led is a very versatile fixture suitable for most installation settings. A rigorous design and compact dimensions help reduce the visual impact of its structure leaving the scene to the even and well defined light emission. Designers looking for a valid element to create precious atmospheres will find in Ola led a suitable solution.



SPECIFICATION SHEET

LEDOLOGY[®]

A **Luminart** BRAND

WWW.LUMINARTLIGHTING.COM

OLA

LED Exterior

TYPE:

PROJECT NAME:



L.2210923
9 COOL WHITE LED 9x1W
Electronic power supply included
<< 80°C



9x



30°

WIDE BEAM

L.2211023
9 WARM WHITE LED 9x1W
Electronic power supply included
<< 80°C



9x



30°

WIDE BEAM

L.2211123
9 BLUE LED 9x1W
Electronic power supply included
<< 80°C



9x



30°

WIDE BEAM

On request lens with narrow beam 8° (N)



SPECIFICATION SHEET

LEDOLOGY[®]

A **Luminart** BRAND

WWW.LUMINARTLIGHTING.COM

OLA

LED Exterior

TYPE:

PROJECT NAME:

Description

Outdoor luminaire for installation on wall. Configuration: phospho-chromatised and polyester powder coated die-cast aluminium structure (four colours available), tempered sandblasted or transparent glass, pure aluminium optics, silicone gasket and stainless steel screws.

Versions available

Finish-frames designs:

- all light

Diffuser: transparent glass (VT)

Light sources

9 led module 9W (cool-white 5500°K, warm-white 3000°K, and blue 475nm) (transformer integrated into the module)

Dimensions

Length: 150mm

Height: 150mm

Width: 100mm

Technical features

Protection Rating: IP65 • In compliance with EN 60598-1

Class of insulation: I

Installation

Wiring through a M16 cable gland ($\varnothing < 10\text{mm}$ cables). Outdoor use requires suitable flexible cables assuring the watertightness of the cable gland.

Colours available



1 White



2 Aluminium



3 Anthracite



4 Black



Wall fitting



ceiling fitting



The fitting is equipped with 1 cable input



Protection against impact.
IK 08 - 5,00 joule

