

# OLA™

LED Exterior

**TYPE:**

**PROJECT NAME:**

Ola led is a very versatile fixture suitable for most installation settings. A rigorous design and compact dimensions help reduce the visual impact of its structure leaving the scene to the even and well defined light emission. Designers looking for a valid element to create precious atmospheres will find in Ola led a suitable solution.



SPECIFICATION SHEET

**LEDOLOGY®**

A **Luminart®** BRAND

[WWW.LUMINARTLIGHTING.COM](http://WWW.LUMINARTLIGHTING.COM)

# OLA™

LED Exterior

**TYPE:**

**PROJECT NAME:**



L.2210923  
9 COOL WHITE LED 9x1W  
Electronic power supply included  
<< 80°C



9x



30° WIDE BEAM

L.2211023  
9 WARM WHITE LED 9x1W  
Electronic power supply included  
<< 80°C



9x



30° WIDE BEAM

L.2211123  
9 BLUE LED 9x1W  
Electronic power supply included  
<< 80°C



9x



30° WIDE BEAM

On request lens with narrow beam 8° (N)



SPECIFICATION SHEET

**LEDOLOGY®**

A **Luminart®** BRAND

WWW.LUMINARTLIGHTING.COM

### Description

Outdoor luminaire for installation on wall. Configuration: phospho-chromatised and polyester powder coated die-cast aluminium structure (four colours available), tempered sandblasted or transparent glass, pure aluminium optics, silicone gasket and stainless steel screws.

### Versions available

Finish-frames designs:

- all light

Diffuser: transparent glass (VT)

### Light sources

9 led module 9W (cool-white 5500°K, warm-white 3000°K, and blue 475nm) (transformer integrated into the module)

### Dimensions

Length: 150mm

Height: 150mm

Width: 100mm

### Technical features

Protection Rating: IP65 • In compliance with EN 60598-1

Class of insulation: I

### Installation

Wiring through a M16 cable gland ( $\varnothing < 10\text{mm}$  cables). Outdoor use requires suitable flexible cables assuring the watertightness of the cable gland.

### Colours available



Wall fitting



ceiling fitting



The fitting is equipped with 1 cable input



Protection against impact.  
IK 08 - 5,00 joule

