



INSTRUCTION

- Switch off the power or pull the plug out.
- Unscrew the handle (A) and lower the canopy (B). (Fig.A)
- Fix the bracket (C) with screw (D) and dowels (E) on the ceiling. (Fig.A)
- Adjust the length of the steel cable acting on regulating terminal security (G), push the part (B) of the gripper so that the steel cable runs. (Fig.A)
- Connect the wires to terminal (F) according to the polarity, and close the box. (Fig.A)
- Tense the power cable paying attention to the regulation, it doesn't have to be too tense
- Place the canopy in the ceiling. Screw with care the lock (A), the block cable (G). (Fig.B)
- Attached the bulb to bulb socket.
- Insert the transparent tube (H) around the coloured internal tube (I) and fix it screwing the screws (L) in particular (M).

ATTENTION

The products of our production are suitable for the using in usual surroundings with standard temperature and humidity levels.
All the operations have to be done by a technician.

CLEANING

Switch off the power or pull the plug out.

For the periodical cleaning of the lamp use always gloves and a soft cloth (for glossy surfaces) or a feather duster for the lampshade in fabric or pleated fabric. Don't use aggressive solvents or alcohol. Avoid absolutely to fold parts which are not expected for folding, in this case welded parts are going to be damaged.



1 x max 100W E27 spot R80



1 x max 29W E27 fluo