

MODEL #

FINISH

LED COLOUR

OPTIC

WATTAGE

DRIVER

VOLTAGE



Segnapasso da incasso a parete, ideale per l'illuminazione di gradini e corridoi.


Recessed wall spotlight, ideal for the lighting of steps and corridors.

Materiale	Corpo in alluminio anticorodal N° 2 finiture standard	
N° Led	1 x 1/2W	
Potenza assorbita	1/2W	
Collegamento	In serie rispettando la polarità	
Cablaggio	Fornito con 25 cm di cavo	
Installazione	- Muratura con scatola da incasso 503 (<i>non inclusa</i>) e viti M3 a scomparsa (<i>fornite</i>) - Cartongesso/Legno con molle (<i>non incluse</i>)	
Driver switching	(<i>non inclusa</i>) 350mA (1W)	p. 424
	(<i>non inclusa</i>) 500mA (2W)	p. 425
Accessori	Molla cod. ML060	p. 402

Material	Anticorodal aluminium body No. 2 standard finishings	
Led no.	1 x 1/2W	
Power absorption	1/2W	
Connection	Series connection respecting polarities	
Wiring	Provided with a 25cm long cable	
Installation	- On brickwork through a 503 box (<i>not included</i>) and screws M3 (<i>included</i>) - On false ceiling/wood with springs (<i>not included</i>)	
Driver switching	(<i>not included</i>) 350mA (1W)	p. 424
	(<i>not included</i>) 500mA (2W)	p. 425
Accessories	Spring code ML060	p. 402

alisea

IP40 CE M M F III kg 0,400



CODE	OPTIONS	SUPPLY	N° LED	LED COLOUR	OPTICS	WATT	FINISHING
L6ALI
	0	I CC	1	1 6000°K 2 4000°K 3 3000°K W 2700°K 4 Red 5 Green 6 Blue	1 15°	1 2	A Anod. alu. B White RAL9003