

# BRITE XT™

LED SUBMERSIBLE


TYPE:

PROJECT NAME:

IP68 IK09




Intertek (5.86")



L01C8135

PVC Housing

kg 1,02



## ELECTRICAL FEATURES

POWER CONSUMPTION	Standard version: <b>24W</b> - RGB version: <b>12-24W</b>
POWER SUPPLY	Standard version: <b>24Vdc</b> - RGB version: <b>C.C.</b>
POWER SUPPLY UNIT	<b>24W - 24Vdc</b> (Driver installed remotely)
DIMMING	DMX, 1-10V, phase cut dimmable (except RGB version)
CONNECTION	Parallel connections for 24V and Series connection for Constant Current

## LIGHTING FEATURES

LED COLOUR	<b>Amber, 2200K, 2700K, 3000K, 4000K, 5000K, Red, Green, Blue, RGB</b>
CRI	<b>&gt;90</b> (2700K, 3000K, 4000K, 5000K)
OPTICS	<b>10°, 30°</b>
TOTAL NOMINAL LUMENS	1752lm (2700K)    1860lm (3000K)    2064lm (4000K)
AVERAGE LED LIFE	<b>50.000h L80 B10</b>

## MECHANICAL FEATURES

WEIGHT	<b>kg 3,48</b>
FINISHES	<i>Steel</i>
INSTALLATION	<i>Recessed in ground with housing box (order separately)</i>
MATERIAL	<i>AISI 316L stainless steel body, AISI 316L stainless trim, transparent tempered glass</i>

## GENERAL FEATURES

OPERATING TEMPERATURE	<b>-10°C +45°C</b>
INGRESS PROTECTION	<b>IP68</b>
IMPACT RESISTANCE	<b>IK09</b>
GLOW WIRE TEST	<b>960°C</b>
SCREEN TEMPERATURE	<b>40° @ Ta = 25°</b>
WALKOVER	Yes
DRIVE OVER	Yes
POWER CABLES	<i>Provided with 3 m cable</i>

SPECIFICATION SHEET

**LEDOLOGY®**

A **Luminart** BRAND

WWW.LEDOLOGY.COM

# BRITE XT™

LED SUBMERSIBLE

TYPE:

PROJECT NAME:



SPECIFICATION SHEET

**LEDOLOGY**®

A **Luminart** BRAND

[WWW.LEDOLOGY.COM](http://WWW.LEDOLOGY.COM)