

ECCO™

RECESSED LED

TYPE:

PROJECT NAME:



MODEL #

FINISH

LED COLOUR

OPTIC

WATTAGE

DRIVER

VOLTAGE



Faretto da incasso a parete/ pavimento, ideale per l'illuminazione di gradini, mensole, scaffalature, parquet e superfici in legno.


Recessed wall/ floor spotlight, ideal for the lighting of steps, shelves, parquet and wooden surfaces.

Materiale	Corpo in alluminio anticorrosione Vetro temperato sabbato N° 3 finiture standard
N° Led	1 x 1W
Potenza assorbita	1W
Collegamento	In serie rispettando la polarità
Cablaggio	Fornito con 25 cm di cavo
Installazione	Cartongesso/legno: per interferenza tramite o-ring (fornito) o con molle (<i>non include</i>)
Driver switching	(<i>non inclusa</i>) 350mA (1W) p. 424
Accessori	Molla cod. ML025 p. 402
Fotometrie	p. 406

Material	Anticorrosion aluminium body Satinized tempered glass No. 3 standard finishings
Led no.	1 x 1W
Power absorption	1W
Connection	Series connection respecting polarities
Wiring	Provided with a 25 cm long cable
Installation	On false ceiling/wood through o-ring (included) or springs (<i>not included</i>)
Driver switching	(<i>not included</i>) 350mA (1W) p. 424
Accessories	Spring code ML025 p. 402
Photometries	p. 406

ecco

IP44 CE M/M F III kg 0,015 kg 250 ø mm 27



CODE	OPTIONS	SUPPLY	N°LED	LED COLOUR	OPTICS	WATT	FINISHING
L6ECO
	0	I CC	1	1 6000°K 2 4000°K 3 3000°K W 2700°K 4 Red 5 Green 6 Blue	4 120°	1	A Anod. alu. B White RAL9003 C Chromium-plated

SPECIFICATION SHEET

LEDOLOGY®

A **Luminart** BRAND

WWW.LUMINARTLIGHTING.COM