

# LATY™

WALL/CEILING LED SYSTEM - ADA COMPLIANT

TYPE:

PROJECT NAME:



105°



3000K / 4000K



40



>80



A+



0



Matte black



Satin white



Intertek

## LATY

WALL / CEILING SYSTEM

*Characterized by a dark cut on its surface, which contrasts with the light cast from the sides of the luminaire, Laty is a modular double emission luminaire for wall or ceiling. It is made from epoxy polyester powder coated aluminium and it is equipped with a frosted polycarbonate screen and LED light sources. This fixture requires a 24Vdc remote driver (to be ordered separately) which, for maintenance purposes, must be placed in an inspection box at a distance of no more than 10 metres. Its degree of protection against the penetration of dust, solid objects and liquids is IP40.*

SPECIFICATION SHEET

**LEDOLOGY®**

A **Luminart®** BRAND

WWW.LUMINARTLIGHTING.COM

# LATY™

TYPE:

WALL/CEILING LED SYSTEM - ADA COMPLIANT



PROJECT NAME:

LaTY

CodE	W	Lm (3000K)
L25A7-603.L100...*	2x12 (2x120 led)	2x1200
L25A7-603.L100...*	2x25 (2x280 led)	2x2500
L25A7-004L	End caps (pair)	
L250800/DIM	Dimming kit	
L250800/EM	Emergency kit with batteries	

*\*code per meter*

*remote driver not included*



Multiples of 50 mm\*, max length 4m Cod. L25a7-603.L

Multiples of 30 mm\*, max length 4m Cod. L25a7-604.L

**\*NOTICE:** add 17,4 mm on the total length of the composition.

SPECIFICATION SHEET

**LEDOLOGY®**

A **Luminart®** BRAND

WWW.LUMINARTLIGHTING.COM