LUNATM SMALL


CEILING 32W

TYPE:

PROJECT NAME:



25



Ceiling lamp Ø 430mm (17") with direct light. Aluminum structure matt white, black or brass coated. Opal membrane diffuser. Strip LED.

Power input: 32W Light emmission direction: Direct Materials: Aluminium structure, opal membrane diffuser Electrical: High efficiency electronic power supply, rated 50,000 hours 120V-277V Dimming: Power supply compatible with 0-10V

Structure finish: Matt white, matt black, brass





Light source: LED 3000K: 90CRI 4000K: 90CRI

Degree of protection: IP20

Source lumens: 3648 lm

Source efficacy: 114 lm/W

ORDERING INFO

Model (Order Code) Structure Finish LED Remote Driver Options* OL032670204A20100 32W ○3000K O Matt White ○ 120V 0-10V Dimming O Matt Black ○4000K 277V 0-10V Dimming

O Brass



SHE

*Remote driver installation on Luna ceiling.




LUNATM MEDIUM

CEILING 69W

TYPE:

PROJECT NAME:





Ceiling lamp \emptyset 900mm (35"1/2) with direct light. Aluminum structure matt white, black or brass coated. Opal membrane diffuser. Strip LED.

Power input: 69W

Light emmission direction: Direct / direct and indirect

Materials: Aluminium structure, opal membrane diffuser

Electrical: High efficiency electronic power supply, rated 50,000 hours 120V-277V

Dimming: Power supply compatible with 0-10V

Structure finish: Matt white, matt black, brass





Ø 35"1/2

Light source: LED 3000K: 90CRI 4000K: 90CRI

Degree of protection: IP20

Source lumens: 7866 lm


Source efficacy: 114 lm/W

ORDERING INFO SHE SPECIFICATION Model (Order Code) Structure Finish LED Remote Driver Options* OL032670201A20100 69W ○3000K O Matt White ○ 120V 0-10V Dimming O Matt Black ○4000K 277V 0-10V Dimming O Brass *Remote driver installation on Luna ceiling.



PROJECT NAME:





Ceiling lamp Ø 1250mm (49"1/4) with direct light. Aluminum structure matt white, black or brass coated. Opal membrane diffuser. Strip LED.

Power input: 78W

Light emmission direction: Direct / direct and indirect

Materials: Aluminium structure, opal membrane diffuser

Electrical: High efficiency electronic power supply, rated

50,000 hours 120V-277V

Dimming: Power supply compatible with 0-10V

Structure finish: Matt white, matt black, brass





Light source: LED 3000K: 90CRI 4000K: 90CRI

Degree of protection: IP20

Source lumens: 8892 lm

Source efficacy: 114 lm/W

OF	RDERING INFO	-	-	-
z	Model (Order Code)	Structure Finish	LED	Remote Driver Options*
IFICATIO	L032670211A20100 78W	○ Matt White○ Matt Black○ Brass	○ 3000K ○ 4000K	○ 120V 0-10V Dimming ○ 277V 0-10V Dimming
Intert	tek			*Remote driver installation on Luna ceiling.

