# **LUNATM SMALL**

### TYPE:

WALL 32W

#### **PROJECT NAME:**





Ø 432 0 477"

Wall lamp  $\emptyset$  430mm (17") with direct light. Aluminium structure matt white, black or brass coated. Opal membrane diffuser. Strip LED.

Power input: 32W
Light emmission direction: Direct
Materials: Aluminium structure, opal membrane diffuser
<b>Electrical:</b> High efficiency electronic power supply, rated 50,000 hours 120V-277V
Dimming: Power supply compatible with 0-10V
Structure finish: Matt white, matt black, brass

**Light source:** LED 3000K: 90CRI 4000K: 90CRI

Degree of protection: IP20

Source lumens: 3648 lm

Source efficacy: 114 lm/W





ш	١
ш	
工	
S	
_	
Z	
0	
_	
7	
Ò	
$\simeq$	
ш	
$\overline{\Box}$	

Model (Order Code)	Structure Finish	LED	Driver Options
O L032670104A20100 32W	O Matt White	○3000K	120V 0-10V Dimming
	○ Matt Black	○4000K	277V 0-10V Dimming
	OBrass		

### LUNA<sup>TM</sup> MEDIUM

#### TYPE:

WALL 69W

#### **PROJECT NAME:**



Ø 900 Ø 35″1/2 25 1"

Wall lamp Ø 900mm (35"1/2) with direct light. Aluminium structure matt white, black or brass coated. Opal membrane diffuser. Strip LED.

Power input: 69W

Light emmission direction: Direct

Materials: Aluminium structure, opal membrane diffuser

Electrical: High efficiency electronic power supply, rated 50,000 hours 120V-277V

Dimming: Power supply compatible with 0-10V

Structure finish: Matt white, matt black, brass

**Light source:** LED 3000K: 90CRI 4000K: 90CRI

Degree of protection: IP20

Source lumens: 7866 lm

Source efficacy: 114 lm/W





<b>ORDERING</b>	INFO
OUDEUING	INFO

Model (Order Code)

Structure Finish

LED

Driver Options

Matt White

Matt Black

Brass



ЕТ

SH

SPECIFICATION



## **LUNA™ LARGE**


#### TYPE:

WALL 78W

#### **PROJECT NAME:**



Wall lamp Ø 1250mm (49"1/4) with direct light. Aluminium structure matt white, black or brass coated. Opal membrane diffuser. Strip LED.



Power input: 78W

Light emmission direction: Direct

Materials: Aluminium structure, opal membrane diffuser

Electrical: High efficiency electronic power supply, rated 50,000 hours 120V-277V

Dimming: Power supply compatible with 0-10V

Structure finish: Matt white, matt black, brass



SPECIFICATION SHEET



Light source: LED
3000K: 90CRI
4000K: 90CRI

Degree of protection: IP20

Source lumens: 8892 lm

Source efficacy: 114 lm/W

ORDERING INFO	_	_	_	
Model (Order Code)	Structure Finish	LED	Driver Options	
O L032670111A20100 78W	<ul><li>○ Matt White</li><li>○ Matt Black</li><li>○ Brass</li></ul>	○ 3000K ○ 4000K	○ 120V 0-10V Dimming ○ 277V 0-10V Dimming	