PASSUM SIDEWARDS™

Ground and wall recessed, ground surface light.

ø 70 LED
2.76"

ø 125 LED
4.92"

ø 180 LED
7.09"

PASSUM adjustable™

Ground recessed, adjustable optic

ø 180 LED
7.09"

PASSUM SIDEWARDS™

Ground + wall recessed, sidewards emitting

GENERAL FEATURES

A range of recessed luminaires in primary low copper content alluminium alloy, painted in double coat polyester powders after phosphochrome, resistant to UV rays and harsh weather conditions.
Dimensions: ø 70/125 and 180mm(7.09").
Remote driver for ø70 mm(2.76"), inside for 125(4.92") and 180mm(7.09").
Side-emitter optic to turn the light along the ground surface.
Led 1/3/4 and 9,5W / CRI 80.
Life: 50.000 h with max decreasing of 30% - L70 B50.
Vandalproof polycarbonate diffuser and surface T≤ 40° C for each model.
Max load pressure allowed 2.000 Kg.
Walk over + driver over allowed.
Light body supplied pre-wired with 0,5 mt in-ground cable H07RN-F and connection block IP68.
The covering canopies are supplied separately, in copper free alluminium with double layer of powders painting, resistant to any bad weather conditions, stainless steel screws.
Four different light emissions 90°/ 2x90° / 180° and 360°.
The version d 180mm(7.09") with fully adjustable optic from 0° to 45° towards up becomes a minimally invasive accent light.
Made according to EN 60598-1:08+A11:09 European standards CE

MAXIMUM MODULARITY

The lighting fittings of the range are supplied in 3 separate parts:
1 - Recessing box
2 - Light body with glass and gasket
3 - Ground/wall drive over canopy.

IN-GROUND WIRING

Any fitting of the range is pre-wired with 0,5 mt H07RN-F cable and IP 68 connetion block IP 68.

WALK OVER AND DRIVE OVER

Max surface T≤ 40°C and load pressure max 2.000Kg.

SIDE EMITTER OPTIC

The lens turns the light and orient the along the ground surface.



CHANGEABLE CANOPIES IN ALUMINIUM

The covering canopies allows to orient the light in 4 different light emissions: 90° / opposite 90° /180 and 360° angle beam.



LIGHT BODY HORIZONTAL REGULATION

After inserting the light body in the recessed box is possible a complete planning regulation, to level out the fitting.



SPECIFICATION SHEET

PASSUM SIDEWARDS™ ø180 (7.09")

Ground + wall recessed for surface light

TYPE: _____

PROJECT NAME:

| IN-GROUND BOX



CODE	/ DESCRIPTION
L981431	/ In-ground box ø 180 mm (7.09")

In-ground box in waterproof technopolymer.

| LIGHT BODY ø 180 mm (7.09")



CODE		/ LAMP	/OPTIC	W	Lm
L981436	○	Led	-	9,5	1200

Driver inside 120V / 350 mA.
T≤ 40°C and max load pressure 2000 Kg.
IK 10 / IP 67 / Class I / 4000K / CRI 80

For 3000 K add TC to the code n.

| COVERING CANOPIES ø 180 mm (7.09")



CODE	/ DESCRIPTION
L981535	/ 1 window
L981536	/ 2 windows 90°
L981537	/ 2 windows 180°
L981539	/ 360° Light

COLOUR AG

1 window



2 windows 90°

2 windows 180°

360° Light

A richiesta l'insieme corpo lampada+flangia viene fornito montato e sigillato.
The set light body+flange can be supplied assembled, sealed and oriented.

SPECIFICATION SHEET