
PEAKTM SUSPENSION Ø500



Technical data	
Light source	LED bulb
Circuit structure	LED bulb
Light emission direction	direct
Power	1x MAX 20W E26
Source lumens	-
Source efficacy	-
Consumption	-
Delivered lumens	-
Luminaire efficacy	-
Secondary	-
Colour temperature	-
Colour rendering index	-
Standard Deviation of Colour Matching	-
Energy class	A
Safety class	I
Degree of protection	IP 20
Direct mounting on normally flammable surfaces	•
Operating temperature	+10° / +40°

TYPE:

PROJECT NAME:



Canopy		
Diameter (Ø)	90 mm - 3" 1/2 inch	
Height	30 mm - 1" 1/8 inch	
Ceiling mount	direct	
Lampshade		
Material	fabric + polycarbonate	
Finish	white, black, or custom color (on request)	

Hanging cables

Stainless steel cables standard length (custom available)	0
Electric cable standard length (custom available)	2500 mm/100"

ЦШ			
SHI	ORDERING INFO	_	
Z O	Model (Order Code)	Finish	Driver Options
IFICATI	○L032550302A00600	○ Black○ White○ Custom	○ 120V Phase Dimming
SPEC	Intertek	Fixture comes with a 4"	backplate that mounts to a standard junction box.
	Luminart [®]	V	ww.luminartlighting.com


PEAKTM SUSPENSION Ø1000



Light source Circuit structure Light emission direction Power 1x MAX Source lumens Source efficacy Consumption Delivered lumens Luminaire efficacy Secondary Colour temperature Colour rendering index Standard Deviation of Colour Matching Energy class Safety class Degree of protection Direct mounting on normally flammable surfaces	
Light emission direction Power 1x MA Source lumens Source efficacy Consumption Delivered lumens Luminaire efficacy Secondary Colour temperature Colour rendering index Standard Deviation of Colour Matching Energy class Safety class Degree of protection	LED bulb
Power 1x MAX Source lumens Source efficacy Consumption Delivered lumens Luminaire efficacy Secondary Colour temperature Colour rendering index Standard Deviation of Colour Matching Energy class Safety class Degree of protection	LED bulb
Source lumens Source efficacy Consumption Delivered lumens Luminaire efficacy Secondary Colour temperature Colour rendering index Standard Deviation of Colour Matching Energy class Safety class Degree of protection	direct
Source efficacy Consumption Delivered lumens Luminaire efficacy Secondary Colour temperature Colour rendering index Standard Deviation of Colour Matching Energy class Safety class Degree of protection	X 20W E26
Consumption Delivered lumens Luminaire efficacy Secondary Colour temperature Colour rendering index Standard Deviation of Colour Matching Energy class Safety class Degree of protection	-
Delivered lumens Luminaire efficacy Secondary Colour temperature Colour rendering index Standard Deviation of Colour Matching Energy class Safety class Degree of protection	-
Luminaire efficacy Secondary Colour temperature Colour rendering index Standard Deviation of Colour Matching Energy class Safety class Degree of protection	-
Secondary Colour temperature Colour rendering index Standard Deviation of Colour Matching Energy class Safety class Degree of protection	-
Colour rendering index Colour rendering index Standard Deviation of Colour Matching Energy class Safety class Degree of protection	-
Colour rendering index Standard Deviation of Colour Matching Energy class Safety class Degree of protection	-
Standard Deviation of Colour Matching Energy class Safety class Degree of protection	-
Energy class Safety class Degree of protection	-
Safety class Degree of protection	-
Degree of protection	A
	I
Direct mounting on normally flammable surfaces	IP 20
	•
Operating temperature	+10° / +40°

TYPE:

PROJECT NAME:



Canopy		
Diameter (Ø)	90 mm - 3" 1/2 inch	
Height	30 mm - 1" 1/8 inch	
Ceiling mount	direct	
Lampshade		
Material	fabric + polycarbonate	
Finish	white, black, or custom color (on request)	

Hanging cables

Stainless steel cables standard length (custom available)	0
Electric cable standard length (custom available)	2500 mm/100"

SHI	ORDERING INFO		
Z O	Model (Order Code)	Finish	Driver Options
FICATI	○L032550301A00600	◯ Black◯ White◯ Custom	○ 120V Phase Dimming
SPECI	Intertek	Fixture comes with a 4"	backplate that mounts to a standard junction box.
	Luminart [®]	v	