

# PIKO™

## SUSPENSION

TYPE:

PROJECT NAME:



"Less is more" and so Piko lets functionality define its essential shape. Hanging luminaire equipped with a Chip On Board technology high efficiency LED light source and driver. Cables for suspension in galvanized steel with a 1.2 mm diameter, 200 cm of three wire electrical cable 3x1 mm<sup>2</sup> and ceiling attachment in painted steel included. Possibility to personalize the product by choosing among the different available reflectors. The degree of protection against the penetration of dust, solid objects and liquids is IP40.




### PIKO

code	W	Lm (3000K)	lifetime	
<b>L25LD090GP...</b>	90	14060	75.000h	L80/B10
<b>L25LD110GP...</b>	110	16645	60.000h	L80/B10
<b>L25LD130GP...</b>	130	19160	50.000h	L80/B10



- SL LED
- AL included
- 120°
- TC .30 per 3000K / .40 per 4000K
- IP 40
- CRI >80
- SDCM 3
- EEI A++
- RG 1
- 08 Frosted white
- 20 Natural anodised
- A Shades not included



### PIKO OPTICS

code		description
<b>2018</b>		Shade in anodized aluminum ø 600 mm (23.62"), h 195 mm (7.67")
<b>2019</b>		Shade in white aluminum ø 600 mm (23.62"), h 195 mm (7.67")

SPECIFICATION SHEET



WWW.LEDOLOGY.COM

A **Luminart** BRAND