

POCKET™

RECESSED

TYPE:

PROJECT NAME:



SPECIFICATION SHEET

Luminart®


WWW.LUMINARTLIGHTING.COM

POCKET™ SMALL

RECESSED

TYPE:

PROJECT NAME:



FIXTURE SPECIFICATIONS

ASSEMBLY / USAGE

Wall recessed installation

PROTECTION

IP 65 - IK 07

BODY

Die-cast aluminum

SCREEN

Pointed glass

SEALS

Molded silicone gasket UV Resist

SCREWS

Stainless steel A2

PAINT / FINISHING

Anti-corrosive UV stabilised polyester powder

ELECTRICAL SPECIFICATIONS

POWER SUPPLY

24Vdc

ABSORBED POWER

2W

SOURCE

LED

CCT LED

2700K / 3000K / 4000K

SOURCE FLUX

280 lm

FIXTURE SOURCE

160 lm

APPARENT EFFICIENCY

57 %

OPERATING TA

50 °

CRI

80

STEP MACADAM

3

LIFE TIME TM-21

L80B10 50000h

BEAM OPENING Diffuse

COLORS



ACCESSORIES



recessed box 502
L 70 x W 50 x H 70
(2.75" x 1.96" x 2.75")

ORDERING INFO

L90POCKET SMALL

502

Model (Order Code)

Finish Options

Accessories

LED

Dimming Options

L90POCKET SMALL

00: Pure White

502: Recessed Box 502

27: 2700K

120V LTE

10: White

30: 3000K

120V-277V 0-10V

24: Bronze

40: 4000K

(Universal Voltage)

25: Rust

01: Black

30: Anthracite

35: Slate Grey

40: Grey

55: Green Cool Mint



SPECIFICATION SHEET

Luminart®


WWW.LUMINARTLIGHTING.COM

POCKET™ MEDIUM

RECESSED

TYPE:

PROJECT NAME:



FIXTURE SPECIFICATIONS

ASSEMBLY / USAGE

Wall recessed installation

PROTECTION

IP 65 - IK 07

BODY

Die-cast aluminum

SCREEN

Pointed glass

SEALS

Molded silicone gasket UV Resist

SCREWS

Stainless steel A2

PAINT / FINISHING

Anti-corrosive UV stabilised polyester powder

ELECTRICAL SPECIFICATIONS

POWER SUPPLY

24Vdc

ABSORBED POWER

4W

CCT LED

2700K / 3000k / 4000k

SOURCE FLUX

560 lm

FIXTURE SOURCE

310 lm

APPARENT EFFICIENCY

55 %

OPERATING TA

50 °

CRI

80

STEP MACADAM

3

LIFE TIME TM-21

L80B10 50000h

BEAM OPENING

Diffuse

COLORS



ACCESSORIES



recessed box 503
L 108 x W 53 x H 74
(4.25" x 2.08" x 2.91")

ORDERING INFO

L90POCKET MEDIUM

503

Model (Order Code)

Finish Options

Accessories

LED

Dimming Options

L90POCKET MEDIUM

00: Pure White

502: Recessed Box 503

27: 2700K

120V LTE

10: White

30: 3000K

120V-277V 0-10V

24: Bronze

40: 4000K

(Universal Voltage)

25: Rust

01: Black

30: Anthracite

35: Slate Grey

40: Grey

55: Green Cool Mint




SPECIFICATION SHEET

POCKET™ LARGE

RECESSED

TYPE:

PROJECT NAME:



FIXTURE SPECIFICATIONS

ASSEMBLY / USAGE

Wall recessed installation

PROTECTION

IP 65 - IK 07

BODY

Die-cast aluminum

SCREEN

Pointed glass

SEALS

Molded silicone gasket UV Resist

SCREWS

Stainless steel A2

PAINT / FINISHING

Anti-corrosive UV stabilised polyester powder

ELECTRICAL SPECIFICATIONS

POWER SUPPLY

24Vdc

ABSORBED POWER

6W

CCT LED

2700K / 3000K / 4000K

SOURCE FLUX

840 lm

FIXTURE SOURCE

460 lm

APPARENT EFFICIENCY

55 %

OPERATING TA

50 °

CRI

80

STEP MACADAM

3

LIFE TIME TM-21

L80B10 50000h

BEAM OPENING Diffuse

COLORS



ACCESSORIES



recessed box 504
L 133 x W 53 x H 74
(5.23" x 2.08" x 2.91")

ORDERING INFO

L90POCKET LARGE

504

Model (Order Code)

Finish Options

Accessories

LED

Dimming Options

L90POCKET LARGE

00: Pure White

502: Recessed Box 504

27: 2700K

120V LTE

10: White

30: 3000K

120V-277V 0-10V

24: Bronze

40: 4000K

(Universal Voltage)

25: Rust

01: Black

30: Anthracite

35: Slate Grey

40: Grey

55: Green Cool Mint



SPECIFICATION SHEET