

MODEL # FINISH LED COLOUR OPTIC WATTAGE DRIVER VOLTAGE




Faretto da incasso a pavimento, ideale per l'illuminazione di marciapiedi, vialetti, pavimentazioni in porfido, giardini.
Recessed floor spotlight, ideal for the lighting of sidewalks, paths, porphyty floorings, gardens.

Materiale	Corpo in alluminio anodizzato Vetro temperato serigrafato N° 1 finitura standard	
N° Led	1 x 4/6W	
Potenza assorbita	4/6W	
Collegamento	In serie rispettando la polarità	
Cablaggio	Fornito con 50cm di cavo in neoprene e pressacavo	
Installazione	A pavimento con cassaforma (non inclusa)	
Driver switching	(non inclusa) 350mA (4W)	p. 424
	(non inclusa) 500mA (6W)	p. 425
Accessori	Cassaforma cod. CA050R	p. 399
	Cassaforma cod. CA050Q	p. 399
Fotometrie		p. 417
Note	Per configurazione RGB vedi p. 431	

Material	Anodized aluminium body Tempered screen-printed glass No. 1 standard finishing	
Led no.	1 x 4/6W	
Power absorption	4/6W	
Connection	Series connection respecting polarities	
Wiring	Provided with 50cm long bipolar neoprene cable + cable gland	
Installation	On the floor with housing box (not included)	
Driver switching	(not included) 350mA (4W)	p. 424
	(not included) 500mA (6W)	p. 425
Accessories	Housing box code CA050R	p. 399
	Housing box code CA050Q	p. 399
Photometries		p. 417
Note	For RGB version see p. 431	


shaped R



IP67 CE F III kg 0,300 kg 500 50mm WP

CODE	OPTIONS	SUPPLY	N°LED	LED COLOUR	OPTICS	WATT	FINISHING
L6SHA
	R Round	I CC	1	2 4000°K 3 3000°K W 2700°K 7 RGB	1 16° 2 40° 3 64° 4 120° W Wall wash 16°x40°	4 6	O Black RAL9005

shaped Q



IP67 CE F III kg 0,400 kg 500 50mm WP

CODE	OPTIONS	SUPPLY	N°LED	LED COLOUR	OPTICS	WATT	FINISHING
L6SHA
	Q Square	I CC	1	2 4000°K 3 3000°K W 2700°K 7 RGB	1 16° 2 40° 3 64° 4 120° W Wall wash 16°x40°	4 6	O Black RAL9005