

SLEEK™

BOLLARD

TYPE:

PROJECT NAME:



SPECIFICATION SHEET

Luminart®


WWW.LUMINARTLIGHTING.COM

SLEEK™ 200

BOLLARD

TYPE:

PROJECT NAME:



FIXTURE SPECIFICATIONS

ASSEMBLY / USAGE

Ground installation

PROTECTION

IP 65 - IK 10

BODY

Extruded aluminum alloy

SCREEN

Pointed glass

SEALS

Closed-cell EPDM rubber

SCREWS

Stainless steel A2

PAINT / FINISHING

Anti-corrosive UV stabilised polyester powder

ELECTRICAL SPECIFICATIONS

DRIVER

Built-in

DRIVER CURRENT

500mA

POWER MODULE LED

13W

ABSORBED POWER

15W

SOURCE

LED

SOURCE FLUX

2100 lm (2200 lm for 4000K)

FIXTURE SOURCE

700 lm (730 lm for 4000K)

APPARENT EFFICIENCY

33 %

OVERVOLTAGE PROTECTION

1kV-2kV

OPERATING TA

50 °

CRI

80

STEP MACADAM

3

LIFE TIME TM-21

L80B10 50000h

BEAM OPENING

Diffuse 360°

COLORS



ACCESSORIES



KIT.031

Ground anchoring system

SPECIFICATION SHEET

ORDERING INFO

L90SLEEK 200

G

Model (Order Code)

L90SLEEK 200

Finish Options

- 00: Pure White
- 01: Black
- 10: White
- 24: Bronze
- 25: Rust
- 30: Anthracite
- 35: Slate Grey
- 40: Grey

Accessories

G: Ground Anchoring System

LED

- 27: 2700K
- 30: 3000K
- 40: 4000K

Dimming Options

- 120V LTE
- 120V-277V 0-10V (Universal Voltage)




SLEEK™ 700

BOLLARD

TYPE:

PROJECT NAME:



FIXTURE SPECIFICATIONS

ASSEMBLY / USAGE

Ground installation

PROTECTION

IP 65 - IK 10

BODY

Extruded aluminum alloy

SCREEN

Pointed glass

SEALS

Closed-cell EPDM rubber

SCREWS

Stainless steel A2

PAINT / FINISHING

Anti-corrosive UV stabilised polyester powder

ELECTRICAL SPECIFICATIONS

DRIVER

Built-in

DRIVER CURRENT

500mA

POWER MODULE LED

13W

ABSORBED POWER

15W

SOURCE

LED

SOURCE FLUX

2100 lm (2200 lm for 4000K)

FIXTURE SOURCE

700 lm (730 lm for 4000K)

APPARENT EFFICIENCY

33 %

OVERVOLTAGE PROTECTION

1kV-2kV

OPERATING TA

50 °

CRI

80

STEP MACADAM

3

LIFE TIME TM-21

L80B10 50000h

BEAM OPENING

Diffuse 360°

COLORS



00 PURE WHITE 01 BLACK 10 WHITE 24 BRONZE 25 RUST 30 ANTHRACITE 35 SLATE GREY 40 GREY

ACCESSORIES



KIT.031

Ground anchoring system

SPECIFICATION SHEET

ORDERING INFO

L90SLEEK 700

G

Model (Order Code)

Finish Options

Accessories

LED

Dimming Options

L90SLEEK 700

- 00: Pure White
- 01: Black
- 10: White
- 24: Bronze
- 25: Rust
- 30: Anthracite
- 35: Slate Grey
- 40: Grey

G: Ground Anchoring System

- 27: 2700K
- 30: 3000K
- 40: 4000K

- 120V LTE
- 120V-277V 0-10V (Universal Voltage)



SLEEK™ 1000


BOLLARD

TYPE:

PROJECT NAME:



Ø120 (Ø4.72")



FIXTURE SPECIFICATIONS

ASSEMBLY / USAGE

Ground installation

PROTECTION

IP 65 - IK 10

BODY

Extruded aluminum alloy

SCREEN

Pointed glass

SEALS

Closed-cell EPDM rubber

SCREWS

Stainless steel A2

PAINT / FINISHING

Anti-corrosive UV stabilised polyester powder

ELECTRICAL SPECIFICATIONS

DRIVER

Built-in

DRIVER CURRENT

500mA

POWER MODULE LED

13W

ABSORBED POWER

15W

SOURCE

LED

SOURCE FLUX

2100 lm (2200 lm for 4000K)

FIXTURE SOURCE

700 lm (730 lm for 4000K)

APPARENT EFFICIENCY

33 %

OVERVOLTAGE PROTECTION

1kV-2kV

OPERATING TA

50 °

CRI

80

STEP MACADAM

3

LIFE TIME TM-21

L80B10 50000h

BEAM OPENING

Diffuse 360°

COLORS



00 PURE WHITE 01 BLACK 10 WHITE 24 BRONZE 25 RUST 30 ANTHRACITE 35 SLATE GREY 40 GREY

ACCESSORIES



KIT.031

Ground anchoring system

SPECIFICATION SHEET

ORDERING INFO

L90SLEEK 1000

G

Model (Order Code)

Finish Options

Accessories

LED

Dimming Options

L90SLEEK 1000

- 00: Pure White
- 01: Black
- 10: White
- 24: Bronze
- 25: Rust
- 30: Anthracite
- 35: Slate Grey
- 40: Grey

G: Ground Anchoring System

- 27: 2700K
- 30: 3000K
- 40: 4000K

- 120V LTE
- 120V-277V 0-10V (Universal Voltage)



Luminart®

WWW.LUMINARTLIGHTING.COM