

MODEL # FINISH LED COLOUR OPTIC WATTAGE DRIVER VOLTAGE




Faretto da incasso a pavimento, ideale per l'illuminazione di marciapiedi, vialetti, pavimentazioni in porfido, giardini.
Recessed floor spotlight, ideal for the lighting of sidewalks, paths, porphyty floorings, gardens.

Materiale	Corpo in alluminio anodizzato nero Vetro temperato trasparente N° 1 finitura standard	
N° Led	1 x 4/6W	
Potenza assorbita	4/6W	
Collegamento	In serie rispettando la polarità	
Cablaggio	Fornito con 50cm di cavo in neoprene e pressacavo	
Installazione	A pavimento con cassaforma (non inclusa)	
Driver switching	(non inclusa) 350mA (4W)	p. 424
	(non inclusa) 500mA (6W)	p. 425
Accessori	Cassaforma cod. CA070R	p. 400
	Cassaforma cod. CA070Q	p. 400
Fotometrie		p. 417
Note	Per configurazione RGB vedi p. 431	

Material	Anodized black aluminium body Tempered transparent glass No. 1 standard finishing	
Led no.	1 x 4/6W	
Power absorption	4/6W	
Connection	Series connection respecting polarities	
Wiring	Provided with 50 cm long bipolar neoprene cable + cable gland	
Installation	On the floor with housing box (not included)	
Driver switching	(not included) 350mA (4W)	p. 424
	(not included) 500mA (6W)	p. 425
Accessories	Housing box code CA070R	p. 400
	Housing box code CA070Q	p. 400
Photometries		p. 417
Note	For RGB version see p. 431	


styled R



IP67 CE F III kg 0,500 500 60 WP

CODE	OPTIONS	SUPPLY	N°LED	LED COLOUR	OPTICS	WATT	FINISHING	FILTER
L6STY
	R Round	I CC	1	2 4000°K 3 3000°K W 2700°K 7 RGB	1 16° 2 40° 3 64° 4 120° W Wall wash 16°x40°	4 6	N Anod. black alu.	HC Honeycomb louver

styled Q



IP67 CE F III kg 0,500 500 60 WP

CODE	OPTIONS	SUPPLY	N°LED	LED COLOUR	OPTICS	WATT	FINISHING	FILTER
L6STY
	Q Square	I CC	1	2 4000°K 3 3000°K W 2700°K 7 RGB	1 16° 2 40° 3 64° 4 120° W Wall wash 16°x40°	4 6	N Anod. black alu.	HC Honeycomb louver