

**SLEEK™**

BOLLARD

TYPE:

PROJECT NAME:



SPECIFICATION SHEET

**Luminart®**


WWW.LUMINARTLIGHTING.COM  
Last updated: 07/08/24

# SLEEK™ 200

BOLLARD

TYPE:

PROJECT NAME:



## FIXTURE SPECIFICATIONS

### ASSEMBLY / USAGE

Ground installation

### PROTECTION

IP 65 - IK 10

### BODY

Extruded aluminum alloy

### SCREEN

Pointed glass

### SEALS

Closed-cell EPDM rubber

### SCREWS

Stainless steel A2

### PAINT / FINISHING

Anti-corrosive UV stabilised polyester powder

## ELECTRICAL SPECIFICATIONS

### DRIVER

Built-in

### DRIVER CURRENT

500mA

### POWER MODULE LED

13W

### ABSORBED POWER

15W

### SOURCE

LED

### SOURCE FLUX

2100 lm (2200 lm for 4000K)

### FIXTURE SOURCE

700 lm (730 lm for 4000K)

### APPARENT EFFICIENCY

33 %

### OVERVOLTAGE PROTECTION

1kV-2kV

### OPERATING TA

50 °

### CRI

80

### STEP MACADAM

3

### LIFE TIME TM-21

L80B10 50000h

### BEAM OPENING

Diffuse 360°

## COLORS



## ACCESSORIES



### KIT.031

Ground anchoring system

SPECIFICATION SHEET

## ORDERING INFO

SLEEK 200		G		
Model (Order Code)	Finish Options	Accessories	LED	Dimming Options
<input type="radio"/> SLEEK 200	<input type="radio"/> 00: Pure White <input type="radio"/> 01: Black <input type="radio"/> 10: White <input type="radio"/> 24: Bronze <input type="radio"/> 25: Rust <input type="radio"/> 30: Anthracite <input type="radio"/> 35: Slate Grey <input type="radio"/> 40: Grey	<input type="radio"/> G: Ground Anchoring System	<input type="radio"/> 27: 2700K <input type="radio"/> 30: 3000K <input type="radio"/> 40: 4000K	<input type="radio"/> 120V LTE <input type="radio"/> 120V-277V 0-10V (Universal Voltage)



# SLEEK™ 700


BOLLARD

TYPE:

PROJECT NAME:



Ø120 (Ø4.72")



## FIXTURE SPECIFICATIONS

### ASSEMBLY / USAGE

Ground installation

### PROTECTION

IP 65 - IK 10

### BODY

Extruded aluminum alloy

### SCREEN

Pointed glass

### SEALS

Closed-cell EPDM rubber

### SCREWS

Stainless steel A2

### PAINT / FINISHING

Anti-corrosive UV stabilised polyester powder

## ELECTRICAL SPECIFICATIONS

### DRIVER

Built-in

### DRIVER CURRENT

500mA

### POWER MODULE LED

13W

### ABSORBED POWER

15W

### SOURCE

LED

### SOURCE FLUX

2100 lm (2200 lm for 4000K)

### FIXTURE SOURCE

700 lm (730 lm for 4000K)

### APPARENT EFFICIENCY

33 %

### OVERVOLTAGE PROTECTION

1kV-2kV

### OPERATING TA

50 °

### CRI

80

### STEP MACADAM

3


### LIFE TIME TM-21

L80B10 50000h

### BEAM OPENING

Diffuse 360°

## COLORS



00 PURE WHITE   01 BLACK   10 WHITE   24 BRONZE   25 RUST   30 ANTHRACITE   35 SLATE GREY   40 GREY

## ACCESSORIES



### KIT.031

Ground anchoring system

## ORDERING INFO

SLEEK 700

G

Model (Order Code)

Finish Options

Accessories

LED

Dimming Options

SLEEK 700

00: Pure White

G: Ground Anchoring System

27: 2700K

120V LTE

01: Black

30: 3000K

120V-277V 0-10V

10: White

40: 4000K

(Universal Voltage)

24: Bronze

25: Rust

30: Anthracite

35: Slate Grey

40: Grey



SPECIFICATION SHEET

**Luminart®**

WWW.LUMINARTLIGHTING.COM

Last updated: 07/08/24

# SLEEK™ 1000


BOLLARD

TYPE:

PROJECT NAME:



Ø120 (Ø4.72")



## FIXTURE SPECIFICATIONS

### ASSEMBLY / USAGE

Ground installation

### PROTECTION

IP 65 - IK 10

### BODY

Extruded aluminum alloy

### SCREEN

Pointed glass

### SEALS

Closed-cell EPDM rubber

### SCREWS

Stainless steel A2

### PAINT / FINISHING

Anti-corrosive UV stabilised polyester powder

## ELECTRICAL SPECIFICATIONS

### DRIVER

Built-in

### DRIVER CURRENT

500mA

### POWER MODULE LED

13W

### ABSORBED POWER

15W

### SOURCE

LED

### SOURCE FLUX

2100 lm (2200 lm for 4000K)

### FIXTURE SOURCE

700 lm (730 lm for 4000K)

### APPARENT EFFICIENCY

33 %

### OVERVOLTAGE PROTECTION

1kV-2kV

### OPERATING TA

50 °

### CRI

80

### STEP MACADAM

3


### LIFE TIME TM-21

L80B10 50000h

### BEAM OPENING

Diffuse 360°

## COLORS



00 PURE WHITE   01 BLACK   10 WHITE   24 BRONZE   25 RUST   30 ANTHRACITE   35 SLATE GREY   40 GREY

## ACCESSORIES



### KIT.031

Ground anchoring system

SPECIFICATION SHEET

## ORDERING INFO

SLEEK 1000

G

Model (Order Code)

Finish Options

Accessories

LED

Dimming Options

SLEEK 1000

- 00: Pure White
- 01: Black
- 10: White
- 24: Bronze
- 25: Rust
- 30: Anthracite
- 35: Slate Grey
- 40: Grey

G: Ground Anchoring System

- 27: 2700K
- 30: 3000K
- 40: 4000K

- 120V LTE
- 120V-277V 0-10V (Universal Voltage)



**Luminart®**

WWW.LUMINARTLIGHTING.COM  
Last updated: 07/08/24