TYPE:

CEILING

PROJECT NAME:





CEILING

TYPE:

PROJECT NAME:



Finish options:

Black, White, Dust, Terracotta, Ocean Grey, Gold

Black White	Dust	Terracotta	Ocean Grey	Gold
-------------	------	------------	---------------	------

Input [W]		21W
Lum. flux of light source [lm]	107°	2407 lm

Flot is like a good friend: it will never let you down. This lamp will shine with a bright, even, and wide stream of light for a long time, pleasantly illuminating your interior. To maintain the minimalist design of this luminaire, we have removed all visible mounting elements. Choose from 2 sizes.

Color rendering: CRI 90

Materials: Aluminum


Ingress protection: IP20

Electrical: High efficiency electronic power supply, rated

50,000 hours 120V-277V

SHEET

SPECIFICATION



ORDERING INFO L543.4248 LED **Dimming Options** Model (Order Code) Structure Finishes Optic Options OL543.4248 21W 12: Black ○ 107: 107° ○30:3000K ○ 120V LTE O 13: White ○40: 4000K O 120V-277V 0-10V 21: Terracotta 22: Ocean Grey ○ 23: Dust O 80: Gold





Finish options:

Black, White, Dust, Terracotta, Ocean Grey, Gold

Black White	Dust	Terracotta	Ocean Grey	Gold
-------------	------	------------	---------------	------

Input [W]		50W
Lum. flux of light source [lm]	107°	5805 lm

Flot is like a good friend: it will never let you down. This lamp will shine with a bright, even, and wide stream of light for a long time, pleasantly illuminating your interior. To maintain the minimalist design of this luminaire, we have removed all visible mounting elements. Choose from 2 sizes.


Color rendering: CRI 90

Materials: Aluminum

Ingress protection: IP20

Electrical: High efficiency electronic power supply, rated

50,000 hours 120V-277V



ORDERING INFO				
L543.4254	=	-	-	-
Model (Order Code)	Structure Finishes	Optic Options	LED	Dimming Options
◯ L543.4254 50W	12: Black	○ 107: 107°	○30:3000K	○ 120V LTE
	13: White		○ 40: 4000K	○ 120V-277V 0-10V
	○ 21: Terracotta			
	22: Ocean Grey			
	○ 23: Dust			
	○ 80: Gold			Interte



SPECIFICATION SHEET



