# **SIKT**<sup>TM</sup>

## **ACOUSTICAL SUSPENSION**

#### **PROJECT NAME:**

**TYPE:** 

light source size	
wattage 30 W (↑9 W ↓21 W)	
luminous flux ↑1000 lm ↓2100 lm	
UGR <18	

luminaire size	Ø 1200×140		
	(47.24"x5.51")		
light source size	Ø 450×82 (17.71"x3.22")		
wattage	30 W (↑9 W ↓21 W)		
luminous flux	1000 lm ↓2100 lm		
UGR	<18		



#### Technical information
















light distribution - up	100°
light distribution - down	95°
luminous efficiency	110 lm/W
electrical control	TRIAC
	0-10V
color temperature	3000 K
	4000 K
LED module housing finish	black 7021
	white 9003
shade fabric option	see next page









ORDERING INFO	OI	RDE	RING	3 IN	FO
---------------	----	-----	------	------	----

í		-	-		-
	Model (Order Code)	LED	LED Module Housing Finish	Shade Fabric Options	Driver Options
-	O Sikt L72-1200 30W	○3000K	○ Black 7021	See next page	○ 120V Phase Dimming
5		○ 4000K	○ White 9003		120V 0-10V Dimming
:					277V 0-10V Dimming



SPECIFICATION SHEET



#### **PROJECT NAME:**

### Fabric pallete: ecoPET 12mm

These high-quality sound panels are robust, durable, and have a slightly textile surface that can be washed. They have excellent sound-absorbing properties, are flame-resistant and recyclable. Furthermore, they are environmentally friendly as they are made from recycled PET bottles

