# SOL<sup>TM</sup> SQ

#### TYPE:

**ACOUSTICAL SUSPENSION** 

#### **PROJECT NAME:**



## **SOLTM SQ**

### **ACOUSTICAL SUSPENSION**

luminaire size	1150×1150×12 (45.27"x45.27"x0.47")	
light source size	600×600 (23.62"x23.62")	
wattage	↓40 W	
luminous flux	↓4512 lm	
UGR	<19	

#### **TYPE:**

#### **PROJECT NAME:**

#### **Technical information**












STANDARD	

light distribution - down	90°
luminous efficiency	114 lm/W
electrical control	TRIAC
	0-10V
color temperature	3000 K
	4000 K
LED module housing finish	white 9010
shade fabric option	see next page







_	ORDERING INFO				
SHEE	Model (Order Code)		LED Module Housing Finish	Shade Fabric Options	Driver Options
CIFICALION	O Sol SQ L72-1200 40W	○ 3000K ○ 4000K	○ White 9010	See next page	<ul><li>120V Phase Dimming</li><li>120V 0-10V Dimming</li><li>277V 0-10V Dimming</li></ul>
ᄱ	Intertek				

#### **PROJECT NAME:**

#### Fabric pallete: ecoPET 12mm

These high-quality sound panels are robust, durable, and have a slightly textile surface that can be washed. They have excellent sound-absorbing properties, are flame-resistant and recyclable. Furthermore, they are environmentally friendly as they are made from recycled PET hottles

