

POP HOST™

CEILING / WALL

TYPE:

PROJECT NAME:



SPECIFICATION SHEET

Luminart®


WWW.LUMINARTLIGHTING.COM
Last updated: 04/15/25

POP HOST™

CEILING / WALL

TYPE:

PROJECT NAME:



☐	Up	Down	Diffuser color
KS			Black/Brass
WS			White/Brass
BS			Blue/Brass
GS			Green/Brass
PS			Rose/Brass
RS			Red/Brass

Power		E26
Luminaire Light Flux	2700K	470 lm

Color rendering: CRI >80

Ingress protection: IP20

Electrical: High efficiency electronic power supply, rated 50,000 hours 120V-277V

ORDERING INFO

Model (Order Code)	Finish Options	Driver Options
☐ L173H32W.12L Ø12.6"	☐ KS: Black / Brass	☐ 120V LTE
☐ L173H80W.12L Ø31.5"	☐ WS: White / Brass	
	☐ BS: Blue / Brass	
	☐ GS: Green / Brass	
	☐ PS: Rose / Brass	
	☐ RS: Red / Brass	

Fixture comes with a 4" backplate that mounts to a standard junction box.



SPECIFICATION SHEET

Luminart®

WWW.LUMINARTLIGHTING.COM
Last updated: 04/15/25