

SLEEK™

BOLLARD

TYPE:

PROJECT NAME:



SPECIFICATION SHEET

Luminart®


WWW.LUMINARTLIGHTING.COM

SLEEK™ 200

BOLLARD

TYPE:

PROJECT NAME:



FIXTURE SPECIFICATIONS

ASSEMBLY / USAGE

Ground installation

PROTECTION

IP 65 - IK 10

BODY

Extruded aluminum alloy

SCREEN

Pointed glass

SEALS

Closed-cell EPDM rubber

SCREWS

Stainless steel A2

PAINT / FINISHING

Anti-corrosive UV stabilised polyester powder

ELECTRICAL SPECIFICATIONS

DRIVER

Built-in

DRIVER CURRENT

500mA

POWER MODULE LED

13W

ABSORBED POWER

15W

SOURCE

LED

SOURCE FLUX

2100 lm (2200 lm for 4000K)

FIXTURE SOURCE

700 lm (730 lm for 4000K)

APPARENT EFFICIENCY

33 %

OVERVOLTAGE PROTECTION

1kV-2kV

OPERATING TA

50 °

CRI

80

STEP MACADAM

3

LIFE TIME TM-21

L80B10 50000h

BEAM OPENING

Diffuse 360°

COLORS



ACCESSORIES



KIT.031

Ground anchoring system

ORDERING INFO

G				
Model (Order Code)	Finish Options	Accessories	LED	Dimming Options
<input type="radio"/> L90420F0	<input type="radio"/> 00: Pure White <input type="radio"/> 01: Black <input type="radio"/> 10: White <input type="radio"/> 24: Bronze <input type="radio"/> 25: Rust <input type="radio"/> 30: Anthracite <input type="radio"/> 35: Slate Grey <input type="radio"/> 40: Grey	<input type="radio"/> G: Ground Anchoring System	<input type="radio"/> 27: 2700K <input type="radio"/> 30: 3000K <input type="radio"/> 40: 4000K	<input type="radio"/> 120V LTE <input type="radio"/> 120V-277V 0-10V (Universal Voltage)




SLEEK™ 700

BOLLARD

TYPE:

PROJECT NAME:



FIXTURE SPECIFICATIONS

ASSEMBLY / USAGE

Ground installation

PROTECTION

IP 65 - IK 10

BODY

Extruded aluminum alloy

SCREEN

Pointed glass

SEALS

Closed-cell EPDM rubber

SCREWS

Stainless steel A2

PAINT / FINISHING

Anti-corrosive UV stabilised polyester powder

ELECTRICAL SPECIFICATIONS

DRIVER

Built-in

DRIVER CURRENT

500mA

POWER MODULE LED

13W

ABSORBED POWER

15W

SOURCE

LED

SOURCE FLUX

2100 lm (2200 lm for 4000K)

FIXTURE SOURCE

700 lm (730 lm for 4000K)

APPARENT EFFICIENCY

33 %

OVERVOLTAGE PROTECTION

1kV-2kV

OPERATING TA

50 °

CRI

80

STEP MACADAM

3

LIFE TIME TM-21

L80B10 50000h

BEAM OPENING

Diffuse 360°

COLORS



ACCESSORIES



KIT.031

Ground anchoring system

ORDERING INFO

Model (Order Code)	Finish Options	Accessories	LED	Dimming Options
<input type="radio"/> L90420F1	<input type="radio"/> 00: Pure White <input type="radio"/> 01: Black <input type="radio"/> 10: White <input type="radio"/> 24: Bronze <input type="radio"/> 25: Rust <input type="radio"/> 30: Anthracite <input type="radio"/> 35: Slate Grey <input type="radio"/> 40: Grey	<input type="radio"/> G: Ground Anchoring System	<input type="radio"/> 27: 2700K <input type="radio"/> 30: 3000K <input type="radio"/> 40: 4000K	<input type="radio"/> 120V LTE <input type="radio"/> 120V-277V 0-10V (Universal Voltage)




SLEEK™ 1000

BOLLARD

TYPE:

PROJECT NAME:



FIXTURE SPECIFICATIONS

ASSEMBLY / USAGE

Ground installation

PROTECTION

IP 65 - IK 10

BODY

Extruded aluminum alloy

SCREEN

Pointed glass

SEALS

Closed-cell EPDM rubber

SCREWS

Stainless steel A2

PAINT / FINISHING

Anti-corrosive UV stabilised polyester powder

ELECTRICAL SPECIFICATIONS

DRIVER

Built-in

DRIVER CURRENT

500mA

POWER MODULE LED

13W

ABSORBED POWER

15W

SOURCE

LED

SOURCE FLUX

2100 lm (2200 lm for 4000K)

FIXTURE SOURCE

700 lm (730 lm for 4000K)

APPARENT EFFICIENCY

33 %

OVERVOLTAGE PROTECTION

1kV-2kV

OPERATING TA

50 °

CRI

80

STEP MACADAM

3

LIFE TIME TM-21

L80B10 50000h

BEAM OPENING

Diffuse 360°

COLORS



ACCESSORIES



KIT.031

Ground anchoring system

ORDERING INFO

G				
Model (Order Code)	Finish Options	Accessories	LED	Dimming Options
<input type="radio"/> L90420F2	<input type="radio"/> 00: Pure White <input type="radio"/> 01: Black <input type="radio"/> 10: White <input type="radio"/> 24: Bronze <input type="radio"/> 25: Rust <input type="radio"/> 30: Anthracite <input type="radio"/> 35: Slate Grey <input type="radio"/> 40: Grey	<input type="radio"/> G: Ground Anchoring System	<input type="radio"/> 27: 2700K <input type="radio"/> 30: 3000K <input type="radio"/> 40: 4000K	<input type="radio"/> 120V LTE <input type="radio"/> 120V-277V 0-10V (Universal Voltage)

