


# POP 03 Ø8.0

RECESSED



## TYPE:

## PROJECT NAME:



IP20

L173P03.210.□ GU10 max 50W

L173P03.211.□ GU10 led

L174P03.211.□ GU10 led

With honeycomb

IP20

L173P03.220.□ GU5.3 max 50W

L174P03.220.□ GU5.3 led

With honeycomb

L173KIT.201.050 max 50VA

Dimmable gear: IGBT

IP40

Flicker < 20%

LED 9.5W

CRI>90

L173P03.K.□ dimm IGBT - TRIAC

L174P03.K.□ dimm IGBT - TRIAC

With honeycomb

Led color

Nominal lm

Beam spread

2 = 2700K

710

M = 36°

3 = 3000K

760

S = 24°

### Frame

- 02 Black
- 06 White

### Pop P03

### P

### P1

L173P03.210.□ GU10	11.0 (4.33")	2.5 (0.98")
L173P03.211.□ GU10 led	2.5 (0.98")	
L174P03.211.□ GU10 led + honeycomb	2.5 (0.98")	
L173P03.220.□ GU5.3	9.4 (3.7")	2.5 (0.98")
L174P03.220.□ GU5.3 led + honeycomb	2.5 (0.98")	
L173P03.K.□ led 9.5W IP40	11.4 (4.48")	2.5 (0.98")
L174P03.K.□ led 9.5W IP40 + honeycomb	11.9 (4.68")	2.5 (0.98")

## ORDERING INFO

Model (Order Code)

Finish

LED

Remote Driver Options

- 02 Black
- 06 White

- 2700K
- 3000K

- 120V Phase Dimming
- 120V 0-10V Dimming
- 277V 0-10V Dimming




# POP 03 Ø8.0

RECESSED

TYPE:

PROJECT NAME:



Pop P03	P	P1
L173P03.3 M.□ led IP40	9.0 (3.54")	0.5 (0.19")
L173P03.3 S.□ led IP40	11.0 (4.33")	2.5 (0.98")
L173P03.3 T.□ led IP40	9.0 (3.54")	0.5 (0.19")
L174P03.3 M.□ led IP40 + honeycomb	9.5 (3.74")	0.5 (0.19")
L174P03.3 S.□ led IP40 + honeycomb	11.5 (4.52")	2.5 (0.98")
L174P03.3 T.□ led IP40 + honeycomb	9.5 (3.74")	0.5 (0.19")
L173P03.3WM.□ led IP40	6.8 (2.67")	0.5 (0.19")
L173P03.3WS.□ led IP40	8.8 (3.46")	2.5 (0.98")
L174P03.3WM.□ led IP40 + honeycomb	7.3 (2.87")	0.5 (0.19")
L174P03.3WS.□ led IP40 + honeycomb	9.3 (3.66")	2.5 (0.98")

IP40 ☒ MC-E=3  
350m/A LED 11W CRI>95

L173P03.3 ■▲.□  
L174P03.3 ■▲.□  
With honeycomb

■ Led color Nominal lm □ Beam spread  
2 = 2700K 1195 M = 38°  
3 = 3000K 1257 S = 22°  
4 = 4000K 1313 T = 10°

IP40 ☒ DimToWarm  
350m/A LED 6W CRI 95

L173P03.3W ■▲.□  
L174P03.3W ■▲.□  
With honeycomb

■ Led color Nominal lm □ Beam spread  
W= max 3000K max 445 lm M = 30°  
min. 1800K min. 10 lm S = 18°

Housing for plasterboard Ø 9,5cm (3.74")

- L171Z00.080.01 Single
- L171Z00.080.2L Double
- L171Z00.080.3L Triple

## ORDERING INFO

Model (Order Code)	Finish	LED	Remote Driver Options
	<input type="radio"/> 02 Black	<input type="radio"/> 2700K	<input type="radio"/> 120V Phase Dimming
	<input type="radio"/> 06 White	<input type="radio"/> 3000K	<input type="radio"/> 120V 0-10V Dimming
		<input type="radio"/> 4000K	<input type="radio"/> 277V 0-10V Dimming




# POP 03 Ø8.0 NANO

RECESSED

TYPE:

PROJECT NAME:



17° 359°

IP20 Ø



L173N03.210.□ GU10 max 50W

L173N03.211.□ GU10 led

L174N03.211.□ GU10 led

With honeycomb

IP20 Ø Ø



12V

L173N03.220.□ GU5.3 max 50W

L174N03.220.□ GU5.3 led

With honeycomb

L173KIT.201.050 max 50VA

Dimmable gear: IGBT

IP40

Flicker < 20%



LED 9.5W

CRI>90

L173N03.K.□.□ dimm IGBT - TRIAC

L174N03.K.□.□ dimm IGBT - TRIAC

With honeycomb

■ Led color

Nominal lm

Beam spread

2 = 2700K

710

M = 36°

3 = 3000K

760

S = 24°

□ Frame

02 ● Black

06 ○ White

Pop NaNo N03	P	P1
3N03.210.□	GU10	9.1 (3.58")
3N03.211.□	GU10 led	—
4N03.211.□	GU10 led + honeycomb	—
3N03.220.□	GU5.3	7.5 (2.95")
4N03.220.□	GU5.3 led + honeycomb	—
3N03.K.□.□ led 9,5W IP40	10.0 (3.93")	0.5 (0.19")
4N03.K.□.□ led 9,5W IP40 + honeycomb	10.5 (4.13")	0.5 (0.19")

## ORDERING INFO

Model (Order Code)	Finish	LED	Remote Driver Options
	<input type="radio"/> 02 Black <input type="radio"/> 06 White	<input type="radio"/> 2700K <input type="radio"/> 3000K	<input type="radio"/> 120V Phase Dimming <input type="radio"/> 120V 0-10V Dimming <input type="radio"/> 277V 0-10V Dimming




# POP 03 Ø8.0 NANO

RECESSED

TYPE:

PROJECT NAME:



Pop Nano N03	P	P1
L173N03.3 M.□ led IP40	6.1 (2.4")	0.5 (0.19")
L173N03.3 S.□ led IP40	6.1 (2.4")	0.5 (0.19")
L173N03.3 T.□ led IP40	6.1 (2.4")	0.5 (0.19")
L174N03.3 M.□ led IP40 + honeycomb	6.6 (2.59")	0.5 (0.19")
L174N03.3 S.□ led IP40 + honeycomb	6.6 (2.59")	0.5 (0.19")
L174N03.3 T.□ led IP40 + honeycomb	6.6 (2.59")	0.5 (0.19")

IP40	MC-E=3	▽ ◊
250mA	LED 8W	CRI>95
L173N03.3 □■■.□		
L174N03.3 □■■.□		
With honeycomb		
■ Led color	Nominal lm	■ Beam spread
2 = 2700K	779	M = 38°
3 = 3000K	819	S = 22°
4 = 4000K	855	T = 10°

Housing for plasterboard Ø 9,5cm (3.74")

- L171Z00.080.01 Single
- L171Z00.080.2L Double
- L171Z00.080.3L Triple

## ORDERING INFO

Model (Order Code)	Finish	LED	Remote Driver Options
	<input type="radio"/> 02 Black <input type="radio"/> 06 White	<input type="radio"/> 2700K <input type="radio"/> 3000K <input type="radio"/> 4000K	<input type="radio"/> 120V Phase Dimming <input type="radio"/> 120V 0-10V Dimming <input type="radio"/> 277V 0-10V Dimming

